

QUALITY CERTIFICATE

Product name:

TREEX FLEXGUARD



CHARACTERISTICS	UNIT	TREEX FLEXGUARD/ 110		
Structural:				
Polymer		PP		
Colour		black		
Configuration of net		diamond		
Additives anti-UV		yes		
Nominal mesh size	mm	3x3		
Weight of net	g/m ²	240±5	240±5	240±5
Presentation:				
Nominal diameter min	cm	6	11	15
Nominal height	cm	110±2	110±2	110±2
Packing	pieces/unit	8	6	3
	pieces / bag	200	120	75
	pieces / pallet	2800	1920	1050
	bag / pallet	14	16	14
Expected life time: Resistance against UV at Central European weather conditions min.	year	5	5	5

Other issues to be considered

- This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described on their suitability for a particular application.
- If the product is stored in UV protected, closed and covered place, it retains the mechanical and technical characteristics indefinitely.
- Regarding handling, special treatment is not required.
- All data insert in this sheet must be considered with some tolerance.
- The products' technical characteristics can change in function of the range evolution (modification of the product: design, colours, dimensions) and of the commercial demand.